



ULTRA EZ-OFF POWER STRIPPER

FEATURES

- Low odor
- Works first time
- Concentrated formula

BENEFITS

- Non-irritating to residents
- Labor saving
- Economical to use

RECOMMENDED USES

Removes frequently burnished floor finishes from asphalt tile, concrete, terrazo, tile, vinyl and VCT. Do not use on linoleum, rubber, marble, wood, painted surface or acid dyed concrete floors. Before using on asphalt, test for softening or color bleeding.



SPECIFICATIONS

Color	: Straw	pH use dilution	: 11.7
Scent/Odor	: Solvent	Phosphorus content	: 0.0%
Character	: Clear, non-viscous liquid	Foam	: Low

IMPORTANT:

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE:

Clean mop, mop bucket, clean rags, automatic scrubber, wet vac, wet floor signs.

DIRECTIONS FOR USE:

1. Use appropriate personal protective equipment. Dilute product as follows: Light build-up of floor finishes: Dilute product between 1:8 (16 fl. oz./gal.) and 1:10 (13 fl. oz./gal.) with cool water. Heavy build-up of floor finishes: Dilute product at 1:6 (24 fl. oz./gal.) with cool water. Heavy Build-up of Concrete Sealers: Dilute product at 1:4 (32 fl. oz./gal) with cool water. 2. Blockade areas to be stripped. Floors will be slippery when stripper is applied. Exercise caution. 3. Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
4. Let stripper solution soak for 5-10 minutes. Agitate with mop to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on the floor. Longer soak times may be necessary in cases of extreme buildup. 5. Hand or machine scrub thoroughly using black pads or stripping brush. 6. Pick-up all of the solution with a clean mop, wet vac or automatic scrubber. 7. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water using a mop and bucket. 8. Let floor dry completely before applying recommended floor sealer or finish.

PACKAGING

This product is available in a 5 gallon pail (100954222).