

Periodic Locker Room Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the locker room.
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris on lockers, benches, mirrors, shelves, walls, chairs, stools, tables, sinks, mirrors, drawers, floors and all highly touched objects.</p> <ol style="list-style-type: none"> Post wet floor signs Remove gross soils using a trigger sprayer with general purpose cleaner and a microfiber cloth. Dust mop or sweep floor area and remove any debris, i.e., paper, gross soil, dirt, gum, etc. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all the surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: No rinsing is required.
Step 7	<ol style="list-style-type: none"> After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- All-purpose cleaner
- Dust mop
- Lobby dust pan and broom
- Bucket with wringer
- Wet mop with handle
- Wet floor sign

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Periodic Weight Room Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the weight room.
Step 3	<p>Gross Soil Removal: Inspect all surfaces, benches, weight machines, barbell stands, barbells, dumbbells, treadmills, stair machines, rowing machines, elliptical machines, all exercise equipment and all highly touched objects for gross soil and body perspiration.</p> <ol style="list-style-type: none"> Post wet floor signs. Remove gross soils using a trigger sprayer with general purpose cleaner and a microfiber cloth. Dust mop, sweep or vacuum the weight room floor area and remove any debris, i.e., paper, gross soil, dirt, gum, hand chalk, etc. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all the surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: Avoid spraying sanitizer on windows and mirrors. No rinsing is required.
Step 7	<ol style="list-style-type: none"> After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- All-purpose cleaner
- Dust mop
- Lobby dust pan and broom
- Bucket with wringer
- Wet mop with handle
- Wet floor sign
- Backpack vacuum – battery or corded

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Periodic Athletic Bus Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the bus.
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris on the floor, seats, ledges, seat belts, wheel chair restraints, stair rail handles, ceilings, kick panels, walls and all highly touched objects.</p> <ol style="list-style-type: none"> Remove gross soils using a trigger sprayer with general purpose cleaner and a microfiber cloth. Sweep floor area or vacuum to remove any dry debris, i.e., paper, gross soil, dirt, gum, etc. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all the interior bus surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: Avoid spraying sanitizer on windows and mirrors. No rinsing is required.
Step 7	<ol style="list-style-type: none"> Clean any over spray from the glass windows using a glass cleaner and a microfiber cloth. After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- All-purpose cleaner
- Glass cleaner
- Bucket with wringer
- Wet mop with handle
- Lobby dust pan and broom
- Gum remover
- 1" scraper

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Periodic Shower Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the shower area.
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris. If hard water deposits, soap scum and visible debris are present in the shower area, you may need to clean the area with a foam gun and garden hose.</p> <ol style="list-style-type: none"> Place floor signs outside shower area. Remove dry debris with a lobby dust pan and broom. Fill the foam gun tank with Spartan Foamy Q&A acid cleaner. Connect garden hose to a water source. Connect the foam gun to the garden hose. Turn on the water and foam down the shower area from top to bottom. Allow chemical to dwell for 5 minutes. Turn the knob on the foam gun to rinse. Rinse the walls and floors with clean water. Squeegee excess water into the floor drain. Remove the foam gun and hose from the shower areas and let dry.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all shower surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: No rinsing is required.
Step 7	<ol style="list-style-type: none"> After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Spartan Foamy Q&A
- Dilution control center
- Wet floor sign
- Foam gun
- Garden hose
- Lobby dust pan and broom
- Microfiber cloth

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Periodic Training Room Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the training room.
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris. Clean tables, benches, sinks, mirrors, folding tables, shelves, floors surfaces, stools, chairs, couches, phones and all highly touched objects.</p> <ol style="list-style-type: none"> Remove gross soils using a trigger sprayer with general purpose cleaner and a microfiber cloth. Post wet floor signs. Dust mop, sweep or vacuum the floor area and remove any debris, i.e., paper, gross soil, dirt, gum, etc. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all the surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: Avoid spraying sanitizer on windows and mirrors. No rinsing is required.
Step 7	<ol style="list-style-type: none"> Clean any over spray from the glass windows using a glass cleaner and a microfiber cloth. After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- All-purpose cleaner
- Glass cleaner
- Bucket with wringer
- Wet mop with handle
- Lobby dust pan and broom
- Gum remover
- 1" scraper

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Periodic Trainer Room Sanitation

Step 1	Put on personal protective equipment (PPE).	<p>Safety Tools</p> <ul style="list-style-type: none"> <input type="checkbox"/> Gloves <input type="checkbox"/> Safety glasses or goggles <input type="checkbox"/> Wet floor signs
Step 2	Collect tools and equipment and proceed to the training room.	
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris on lockers, benches, mirrors, shelves, walls, chairs, stools, tables, sinks, mirrors, drawers, floors and all highly touched objects.</p> <ol style="list-style-type: none"> a. Post wet floor signs. b. Remove gross soils using a trigger sprayer with general purpose cleaner and a microfiber cloth. c. Dust mop, sweep or vacuum the floor area and remove any debris, i.e., paper, gross soil, dirt, gum, etc. d. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor. 	
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.	<p>Product Checklist</p> <ul style="list-style-type: none"> <input type="checkbox"/> Electrostatic sprayer with battery and charger <input type="checkbox"/> Spartan Sani-T-10 Plus <input type="checkbox"/> Microfiber cleaning cloths <input type="checkbox"/> Dilution control center <input type="checkbox"/> Manual trigger sprayer <input type="checkbox"/> All-purpose cleaner <input type="checkbox"/> Dust mop <input type="checkbox"/> Bucket with wringer <input type="checkbox"/> Wet mop with handle <input type="checkbox"/> Wet floor sign <input type="checkbox"/> Corded or battery backpack vacuum
Step 5	<ol style="list-style-type: none"> a. Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. b. Fill the tank with Spartan Sani-T-10 Plus. c. Align the tank grooves into the slide rail, and lower the machine onto the tank. d. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. e. Insert the charged battery into the battery socket and lock in place. f. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. g. Pull the trigger to test that the spray nozzle is functioning. 	
Step 6	Spray all the surfaces and highly touched objects from top to bottom (spray 24" distance from all objects). Refill the tank as necessary. Note: Avoid spraying electronic measuring machines. No rinsing is required.	
Step 7	<ol style="list-style-type: none"> a. After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. b. Disconnect storage tank from sprayer. c. Rinse out the tank. d. Mount the empty tank back onto the sprayer. 	
Step 8	Return supplies to closet. Remove gloves and glasses.	
Step 9	Thoroughly wash your hands.	<p>Note:</p> <ol style="list-style-type: none"> 1. All products must be used in accordance with the manufacturers' directions. 2. Review the SDS sheet of all chemicals used in the workplace. 3. Only use attachments recommended or sold by the manufacturer. 4. Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue. 5. Do not use the electrostatic sprayer when children are present.

Periodic Wrestling Mat Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the wrestling room.
Step 3	<p>Gross Soil Removal:</p> <ul style="list-style-type: none"> a. Unroll the mats and place them on the floor. b. Post wet floor signs. c. Inspect all surfaces for gross soil and debris. d. Dry dust mop the mats. Remove dry debris with a dust pan and counter brush. e. Mix all purpose cleaner or disinfectant in a bucket with a wringer. f. Wet mop floor using a bucket, wringer and mop. g. Allow the mats to dry.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ul style="list-style-type: none"> a. Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. b. Fill the tank with Spartan Sani-T-10 Plus. c. Align the tank grooves into the slide rail, and lower the machine onto the tank. d. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. e. Insert the charged battery into the battery socket and lock in place. f. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. g. Pull the trigger to test that the spray nozzle is functioning.
Step 6	<ul style="list-style-type: none"> a. Clean the bottom of your shoes with a cleaner and microfiber cloth. Place the cloth on the floor at the edge of the mat. b. Spray all mats from the center to the outside edges. Do not walk on the areas of the mats. Refill the tank as necessary. c. Note: Mats should be cleaned and sanitized before and after each practice and before and after each match. No rinsing is required.
Step 7	<ul style="list-style-type: none"> a. After all mats have been sanitized, remove the battery from the sprayer and place it in the approved charger. b. Disconnect storage tank from sprayer. c. Rinse out the tank. d. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- All-purpose cleaner
- Dust mop
- Dust pan and counter brush
- Bucket with wringer
- Wet mop with handle
- Wet floor sign

Note:

1. All products must be used in accordance with the manufacturers' directions.
2. Review the SDS sheet of all chemicals used in the workplace.
3. Only use attachments recommended or sold by the manufacturer.
4. Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
5. Do not use the electrostatic sprayer when children are present.

Periodic Restroom Sanitation

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the restroom.
Step 3	<p>Gross Soil Removal: Inspect all surfaces and fixtures for gross soil and debris on toilets, urinals, partitions, counters, mirrors, floors, door handles, levers, dispensers and all highly touched objects.</p> <ol style="list-style-type: none"> Post wet floor signs. Remove gross soils using a trigger sprayer with a disinfectant cleaner and a microfiber cloth. Clean from top to bottom. Dry before wet. Dust mop or sweep floor area and remove any debris, i.e., paper, gross soil, dirt, gum, etc. Wet mop floor using a bucket, wringer and mop to remove dry or wet debris on the floor.
Step 4	Be sure the electrostatic sprayer battery is fully charged. Only use a Victory Innovations charger.
Step 5	<ol style="list-style-type: none"> Fill the tank by first removing it from the unit by rotating the tank locking collar and pulling the tank release ring under the trigger. The tank can now be removed. Note: You must hold on to the tank when you pull the tank release ring, or the tank will fall to the floor. Fill the tank with Spartan Sani-T-10 Plus. Align the tank grooves into the slide rail, and lower the machine onto the tank. Rotate the tank locking collar until you hear the click of the tank release ring snap into place. Insert the charged battery into the battery socket and lock in place. To insure maximized electrostatic performance, always keep your hand firmly wrapped around the handle in contact with the grounding strap. Pull the trigger to test that the spray nozzle is functioning.
Step 6	Spray all the surfaces and highly touched objects from top to bottom in the restroom (spray 24" distance from all objects). Refill the tank as necessary. Note: No rinsing is required.
Step 7	<ol style="list-style-type: none"> After all areas and fixtures have been sanitized, remove the battery from the sprayer and place it in the approved charger. Disconnect storage tank from sprayer. Rinse out the tank. Mount the empty tank back onto the sprayer.
Step 8	Return supplies to closet. Remove gloves and glasses.
Step 9	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles
- Wet floor signs

Product Checklist

- Electrostatic sprayer with battery and charger
- Spartan Sani-T-10 Plus
- Disinfectant
- Microfiber cleaning cloths
- Dilution control center
- Manual trigger sprayer
- Dust mop
- Bucket with wringer
- Wet mop with handle
- Wet floor sign

Note:

- All products must be used in accordance with the manufacturers' directions.
- Review the SDS sheet of all chemicals used in the workplace.
- Only use attachments recommended or sold by the manufacturer.
- Remove the nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
- Do not use the electrostatic sprayer when children are present.

Step 1	Put on personal protective equipment (PPE).
Step 2	Collect tools and equipment and proceed to the area.
Step 3	Gross Soil Removal: Inspect all turf surfaces for gross soil and debris. Remove debris from the turf and place it in a trash can.
Step 4	<ul style="list-style-type: none"> a. Fill the ATV / Gator polyethylene agricultural sprayers with Spartan Sani-T-10 using a dilution control center. b. Drop the sprayer bars in position. c. Turn the sprayer on. d. Drive the ATV / Gator at 5-6 MPH applying the sanitizer evenly. Use systematic over lapping passes or a figure eight pattern over the turf field. e. Refill the tank as necessary.
Step 5	<ul style="list-style-type: none"> a. After turf has been sanitized, empty and rinse the polyethylene agricultural spray tank with cold water. b. Fill the tank with a gallon of clean rinse water. c. Flush the jets and jet bars with cold water. d. Fold the spray bars into the storage position e. Disconnect tank from the ATV / Gator. f. Return the tank to the storage area.
Step 6	Remove gloves and glasses.
Step 7	Thoroughly wash your hands.

Safety Tools

- Gloves
- Safety glasses or goggles

Product Checklist

- ATV / Gator
- Polyethylene agricultural sprayers with spray bars
- Spartan Sani-T-10 Plus
- Microfiber cleaning cloths
- Dilution control center

Note:

1. All products must be used in accordance with the manufacturers' directions.
2. Review the SDS sheet of all chemicals used in the workplace.
3. Only use attachments recommended or sold by the manufacturer.
4. Remove the spray arm nozzle if it becomes clogged and soak it in vinegar to remove hard water and chemical residue.
5. Do not use the sprayer when children are present.